

XP-002189511

WEEK 1 ISSUED

91 02 / 27 FEB 91

(AM)

C03B 5/187

C03B 7/092

P.D. 23-02-1990

P.

1


DOC

91-013752/02 L01 BEKE/ 26.05.88
 BEKESEVICH YU YA *SU 1544-718-A
 26.05.88-SU-430495 (23.02.90) C03B 05/18
 Molten glass homogeniser - has spiral blades in hollow shaft of
 stirrer directed counter to its rotation sense
 C91-006069

Intensified glass melt homogenisation is ensured with vortex stirring
 sets in the shape of striplike blades mounted in the bore of the stirrer
 shaft close to the nozzles. The direction of turns of the vortex exciter
 is opposed to the sense of stirrer rotation.

The molten glass in the vessel (1) is heated by the system (4) and
 the glass flows into the bore (6) of the shaft (2) via the nozzles (5). At
 the same time, the pneumatic pulsator (8) is fed from the source (9)
 of compressed air to pulse the melt in the cavity (6) of the shaft (2).

USE/ADVANTAGE - In glass prodn. The opposed direction of the
 vortex generating blades of stirrer to the sense of stirrer rotation
 improves stirring action. Bul.7/23.2.90 (3pp Dwg.No. 1/3)



© 1991 DERWENT PUBLICATIONS LTD.
 128, Thoebalds Road, London WC1X 8RP, England
 US Office: Derwent Inc., 1313 Dolley Madison Boulevard,
 Suite 401, McLean, VA22101, USA
 Unauthorised copying of this abstract not permitted